

Cyber Commerce Experts LLC

Visual Portfolio - Technical Product Documentation

1. Compliance Label Example



SureGrip Pro

ALL-PURPOSE CONSTRUCTION ADHESIVE

TECHNICAL DATA SHEET

Product name	Beige
Base material	Synthetic rubber
Viscosity	506,000 – 750,000 0 cP
Application temperature	40°F to 100°F / 4°C to 35°C
Service temperature	-20°F to 150°F / -29°C to 66°C
Open time	15-20 minutes
Full cure time	24-48 hours
Tensile Strength	350 pst

- Strong adhesion to various building materials
- Gap filling properties
- Solvent free

INSTRUCTIONS FOR USE

1. Ensure surfaces are clean and dry.
2. Cut nozzle to the desired bead size and fillet inner seal.
3. Apply adhesive with a caulking gun in a continuous bead.
EAd -25 NtM
4. Join the surfaces together and press firmly.

REFER TO THE SAFETY DATA SHEET (SDS) BEFORE USE.



WARNING

HAZARD STATEMENTS

- Cause skin irritation.
- Serious eye irritator. Avoid contact with eyes. If contact occurs, flush eyes with water for 15 minutes. Seek medical attention if necessary.

PRECAUTIONARY STATEMENTS (P201)

Cyber Commerce Experts LLC

Visual Portfolio - Technical Product Documentation

Label for a fictional construction adhesive product. Includes product specs, handling instructions, safety details, and industrial presentation layout.

Cyber Commerce Experts LLC

Visual Portfolio - Technical Product Documentation

2. Technical Data Sheet (TDS) Example

Product: PowerMax Tool Cleaner 2000

Application: Industrial-grade degreaser for metal tools.

Active Ingredients: Sodium Hydroxide 12%, Isopropanol 18%, Water 70%

Physical State: Liquid

Color: Clear

Odor: Mild Alcohol

Flash Point: 28°C

Storage Instructions: Store in a cool, dry, ventilated area.

Precautions: Wear gloves and safety goggles. Avoid contact with skin and eyes.

Certifications: OSHA Compliant | GHS Classification: Flammable Liquid Category 3

Cyber Commerce Experts LLC

Visual Portfolio - Technical Product Documentation

3. Product Manual Example

Product: SmartPro Cordless Drill X8

Model No: X8-SP2024

Usage Instructions:

- Charge the battery fully before first use.
- Press and hold the power button to operate.
- Use drill speed toggle for soft or hard surfaces.
- Always use proper safety gear when operating.

Maintenance:

- Clean the device with a dry cloth after each use.
- Do not expose to water or direct sunlight.
- Recharge every 3 months if not used.

Warranty: 1-year limited warranty. Visit our website for more info.

Support: support@smartprotools.com